


ECO	ENGR	LET	CHANGE	BY	DATE
			RELEASED		

2. CAPACITOR FOR EVERY 3 PACKS
 1. UNLESS OTHERWISE SPECIFIED:
 RESISTANCE VALUES ARE IN OHMS. CAPACITANCE
 VALUES ARE IN MICROFARADS. RESISTORS ARE 1/4 WATT, ±10%
 NOTES:

3. OPTIONAL PROMS
- | | | |
|----------------|----------------|----------------|
| MC68708 | MC68741 | MC68317 |
| E1 TO E2 | E3 TO E9 | E0 TO E4 |
| E3 TO E8 | E4 TO E7 | E1 TO E2 |
| E4 TO E6 | E5 TO E7 | E5 TO E9 |
| E5 TO E9 | | |
4. MC8T97 OPTIONAL
 5. MC8T26 OPTIONAL
 6. MC7430P OPTIONAL



SEE SPECIFICATIONS, DRAWINGS OR DATASHEETS FOR COMPLETE INFORMATION.
 THIS SCHEMATIC IS UNCLASSIFIED AND IS NOT TO BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM.
 MOTOROLA INC. Semiconductor Products Division
 7430 GULF FREEWAY, CHICAGO, ILLINOIS 60654
 © 1978 MOTOROLA, INC. ALL RIGHTS RESERVED.

SCHEMATIC — BASIC MICROCOMPUTER MODULE EVALUATION KIT II

DESIGNED BY: _____ DATE: _____
 CHECKED BY: _____ DATE: _____

FIGURE A3-b. Microcomputer Module
 A3-3